



<b>Husky 1050 Metal</b>	<b>Husky 1590 Plastic</b>	<b>Husky 1590 Metal</b>	<b>Husky 2150 Plastic</b>	<b>Husky 2150 Metal</b>	<b>Husky 3275 Metal</b>
1 in (25.4 mm)	1-1/2 in (38.1 mm)	1-1/2 in (38.1 mm)	2 in (50.8 mm)	2 in (50.8 mm)	3 in (76.2 mm)
NPT or BSP	ANSI Flange	NPT or BSP	ANSI Flange	NPT or BSP	DIN/ANSI, NPT and BSP
Standard, Smart and Remote	Standard and Remote	Standard and Remote	Standard and Remote	Standard and Remote	Standard
50 gpm (189 lpm)	100 gpm (379 lpm)	100 gpm (379 lpm)	150 gpm (568 lpm)	150 gpm (568 lpm)	275 gpm (1041 lpm)
125 psi (8.6 bar, 0.9 MPa)	120 psi (8.3 bar, 0.8 MPa)	120 psi (8.3 bar, 0.8 MPa)	120 psi (8.3 bar, 0.8 MPa)	120 psi (8.3 bar, 0.8 MPa)	120 psi (8.3 bar, 0.8 MPa)
Aluminum, 316 Stainless Steel, Hastelloy	Polypropylene, PVDF	Aluminum, 316 Stainless Steel	Polypropylene, PVDF	Aluminum, 316 Stainless Steel, Ductile Iron	Aluminum
Coated Aluminum, Polypropylene, Conductive Poly	Coated Aluminum, 316 Stainless Steel	Coated Aluminum, 316 Stainless Steel	Coated Aluminum, 316 Stainless Steel	Coated Aluminum, 316 Stainless Steel	Coated Aluminum
23 lb (10.4 kg) Aluminum	35 lb (16 kg) Polypropylene	33.5 lb (15.2 kg) Aluminum	49 lb (22 kg) Polypropylene	58 lb (26.3 kg) Aluminum	150 lb (68 kg) Aluminum
36.3 - 41 lb (16.5-18.6 kg) Stainless Steel	49 lb (22 kg) PVDF	85 lb (38.6 kg) Stainless Steel	68 lb (31 kg) PVDF	111 lb (50.3 kg) Stainless Steel	
41 lb (18.6 kg) Hastelloy				130 lb (59 kg) Ductile Iron	
0.125 in (3.2 mm)	0.188 in (4.8 mm)	0.188 in (4.8 mm)	0.25 in (6.3 mm)	0.25 in (6.3 mm)	0.375 in (9.4 mm)

**1 inch Pump Family**